


**PRODUCT INFORMATION****Eye Safety Fence ESF**

The Eye Safety Fence (ESF) protective fence system is characterised by its versatile applications. One example is in welding and laser processing lines, especially on a larger scale, as well as processes that require high safety standards. The system is offered in two standard heights (2200 mm and 2700 mm) but can be customised according to project requirements if needed. The ground clearance of 175 mm can be reduced to 20 mm with the ground element.

The well-thought-out technical design allows for lateral tolerance compensation, making installation easy to carry out. Shortening the elements in the width of the panel elements can be done on-site with common assembly tools, without the need for additional work or repainting.

The sheet metal panel elements are hung in the posts, facilitating easy installation by a single person with significant time savings. During assembly, the panel elements overlap, creating a completely light-impenetrable surface. Openings for, for example, the installation of control cabinets are possible.

The posts are made from a shaped tube, and during production, cutouts for hanging the panel elements are already incorporated on the sides. At two locations, there are two bendable tabs that enable grounding.

Optional visibility into the process can be achieved through a window with various fillings, such as polycarbonate or welding protection.

Technical Data Fence system Eye Safety Fence**Sheet metal panel elements** Eye Safety Fence Measurements in mm

Designation	Window Filling	Element Height	Element Width	Center-to-Center Dimension
ESF-FE	Field Element	O/P/SSB/SSG	500	1000, 1500, 2000, 2500, 3000, 3500, 4000
ESF-BE	Ground Element	O/P/SSB/SSG	180	1000, 1500, 2000, 2500, 3000, 3500, 4000

Doors Measurements in mm

Designation	Window Filling	Ground Clearance	Door Height	Clear Width
ESF-FTW	Swinging Door, double-sided	O/P/SSB/SSG	20, 175	2200
ESF-FTWO	Swinging Door, double-sided with transom	O/P/SSB/SSG	20, 175	2700
ESF-STW	Sliding Door, double-sided	O/P/SSB/SSG	20, 175	2200
ESF-STWO	Sliding Door, double-sided with transom	O/P/SSB/SSG	20, 175	2700
ESF-DFTW	Double Swinging Door, double-sided	O/P/SSB/SSG	20, 175	2200
ESF-DFTWO	Double Swinging Door, double-sided with transom	O/P/SSB/SSG	20, 175	2700

Posts Measurements in mm

Designation	Dimension	Height	Base plate
ESF-DP	Passage Post	QR80	2200, 2700
ESF-EPA	External Corner Post	QR80	2200, 2700
ESF-EPI	Internal Corner Post	QR80	2200, 2700
ESF-TP	T-Junction Post	QR80	2200, 2700